

30-MAR-2017

ANC-PANC

5-20

ANCHORAGE 8 (ANC 8) / KNIK 2

ANC 8

RWYs 07L (072°) / 07R (072°) / 15 (147°) / 25L (252°) / 25R (252°) / 33 (327°)

	GS	120	150	180	210	240	270
6.6%	ft/MIN	900	1100	1300	1500	1700	1900

DESIGNATOR	ROUTING	ALTITUDES
ANC 8 118.600		NODLE MNM 13700 initial climb FL200
RWY 07L ①②	JET and ACFT > 20000 lbs at MNM 2000 or D4 TED , whichever is earlier, RT HDG 199° - expect vectors to assigned route/fix All other ACFT at MNM 600 or D4 TED , whichever is earlier, RT HDG 199° - expect vectors to assigned route/fix	
RWY 07R ①②	JET and ACFT 20000 lbs at MNM 2000 or D4 TED , whichever is earlier, RT HDG 199° - expect vectors to assigned route/fix All other ACFT at MNM 600 or D4 TED , whichever is earlier, RT HDG 199° - expect vectors to assigned route/fix	
RWY 15 ②	at MNM 600 RT HDG 199° - expect vectors to assigned route/ fix	
RWYs 25L/25R ②	climb on RWY HDG - expect vectors to assigned route/fix	
RWY 33 6.6% to 3000 (ATC) ②	at MNM 600 LT HDG 299° - expect vectors to assigned route/ fix	

① Advise ATC prior to departure if unable to be established on HDG 199° by D4 TED.

② Expect filed altitude within 10 minutes after departure.